

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A dryer, comprising:
  - a cabinet;
  - a drum provided in the cabinet and ~~configured to be in rotational communication~~
  - with a motor; and
  - a heater assembly coupled to the drum, comprising:
    - a heater case having an air passage formed therein;
    - a plate ~~configured to partition~~ that partitions the air passage into an upper passage and a lower passage; and
    - independent first and second coil arrays provided in the air passage ~~and~~
    - ~~each configured to cross the plate between the upper and lower passages,~~ wherein the first coil array ~~comprises~~ crosses the plate multiple times such that a plurality of first coils of the first coil array are alternately positioned in the upper and lower passages, and the second coil array ~~comprises~~ crosses the plate multiple times such that a plurality of second coils of the second coil array are alternately positioned in the upper and lower passages ~~such that,~~ wherein the first and second coils positioned in the upper passage form an alternating pattern in the upper passage, and the first and second coils positioned in the lower passage form an alternating pattern in the

lower passage, ~~wherein~~ such that each of the plurality of first coils is positioned substantially directly across from a corresponding second coil of the plurality of second coils on the opposite side of the plate.

2. (Previously Presented) The dryer as claimed in claim 1, wherein the plurality of first coils of the first coil array are positioned at a predetermined distance from the plurality of second coils of the second coil array.

3. (Previously Presented) The dryer as claimed in claim 1, wherein the first coil array is symmetrical to the second coil array along a predetermined line of symmetry of the air passage.

4. (Currently Amended) The dryer as claimed in claim 1, wherein ~~each~~ the plurality of first coils of the first ~~and second coil arrays is~~ coil array are electrically connected as a single unit, and the plurality of second coils of the second coil array are electrically connected as a single unit that is separate from the first coil array.

5. (Canceled).

6. (Currently Amended) The dryer as claimed in claim 1, wherein upper and lower portions of each of the first and second coil arrays ~~lie on~~are positioned along centerlines of the upper and lower passages, respectively.

7. (Previously Presented) The dryer as claimed in claim 1, wherein the plurality of coils of the first coil array are positioned at a predetermined interval along an air flow direction from the corresponding plurality of coils of the second coil array.

8. (Canceled)

9. (Previously Presented) The dryer as claimed in claim 1, wherein the first and second coil arrays are configured to be separately controlled.

10. (Currently Amended) A heater assembly for a dryer, comprising:  
a heater case having an air passage formed therein;  
a plate ~~configured to partition~~that partitions the air passage into an upper passage and a lower passage; and  
independent first and second coil arrays provided in the air passage~~—and~~  
~~configured to alternately cross the plate between the upper and lower passages,~~ wherein the first coil array comprises a plurality of first coils alternately positioned in the upper and lower

passages, and the second coil array comprises a plurality of second coils alternately positioned in the upper and lower passages such that the first and second coils positioned in the upper passage form an alternating pattern in the upper passage, and the first and second coils positioned in the lower passage form an alternating pattern in the lower passage, wherein each of the plurality of first coils is positioned substantially directly across from a corresponding second coil of the plurality of second coils on the opposite side of the plate.

11. (Previously Presented) The heater assembly as claimed in claim 10, wherein the plurality of first coils of the first coil array are positioned at a predetermined distance from the plurality of second coils of the second coil array.

12. (Previously Presented) The heater assembly as claimed in claim 10, wherein the first coil array is symmetrical to the second coil array along a predetermined line of symmetry of the air passage.

13. (Currently Amended) The heater assembly as claimed in claim 10, wherein ~~each~~the plurality of first coils of the first and second coil arrays is coil array are electrically connected as a single unit, and the plurality of second coils of the second coil array are electrically connected as a single unit that is separate from the first coil array.

14. (Canceled)

15. (Currently Amended) The heater assembly as claimed in claim 10, wherein upper and lower portions of each coil array ~~lie on~~ are positioned along centerlines of the upper and lower passages, respectively.

16. (Previously Presented) The heater assembly as claimed in claim 10, wherein the plurality of first coils of the first coil array are positioned at a predetermined interval in an airflow direction from the corresponding plurality of second coils of the second coil array.

17. (Canceled).

18. (Previously Presented) The heater assembly as claimed in claim 10, wherein the first and second coil arrays are configured to be separately controlled.

19. (Canceled).

20. (Previously Presented) The dryer as claimed in claim 3, wherein the plate is positioned along the predetermined line of symmetry of the air passage.

21. (Previously Presented) The heater assembly as claimed in claim 12, wherein the plate is positioned along the predetermined line of symmetry of the air passage.

22. (Canceled)

23. (Previously Presented) A dryer comprising the heater assembly of claim 10.

24. (Currently Amended) A heater assembly for a dryer, comprising:

a heater case;

a plate provided in the case ~~and configured so as~~ to partition the case into an upper portion and a lower portion;

a first coil array comprising a plurality of first coils, the plurality of first coils comprising a plurality of upper first coils positioned in the upper portion of the case, and a plurality of lower first coils positioned in the lower portion of the case; and

a second coil array comprising a plurality of second coils, the plurality of second coils comprising a plurality of upper second coils positioned in the upper portion of the case, and a plurality of lower second coils positioned in the lower portion of the case, wherein the plurality of upper first and second coils are arranged in the upper portion such that an upper first coil is disposed between two upper second coils and an upper second coil is disposed between two upper first coils so as to form an alternating pattern of upper first and second coils in the upper

portion, and the plurality of lower first and second coils are arranged in the lower portion such that a lower first coil is disposed between two lower second coils and a lower second coil is disposed between two lower first coils so as to form an alternating pattern of lower first and second coils in the lower portion.

25. (Previously Presented) The heater assembly as claimed in claim 24, wherein the first coil array is configured to operate as a single unit, and wherein the plurality of first coils are arranged in the first coil array such that the upper and lower first coils form an alternating pattern.

26. (Currently Amended) The heater assembly as claimed in claim 25, wherein the first coil array ~~is configured to cross~~crosses the plate ~~as each time~~so as to alternately position first coils in the upper and lower passages.

27. (Previously Presented) The heater assembly as claimed in claim 26, wherein the second coil array is configured to operate as a single unit independent of the first coil array, and wherein the plurality of second coils are arranged in the second coil array such that the upper and lower second coils form an alternating pattern.

28. (Previously Presented) The heater assembly as claimed in claim 27, wherein the alternating pattern formed by the upper and lower first coils is a mirror image of the alternating pattern formed by the upper and lower second coils.

29. (Currently Amended) The heater assembly as claimed in claim 27, wherein the second coil array is configured to cross the plate ~~at~~ each time the second coil array alternates between the upper and lower second coils.

30. (Canceled).

31. (Previously Presented) The heater assembly as claimed in claim 24, wherein the first and second coil arrays each form a zigzag pattern.

32. (Previously Presented) A dryer comprising the heater of claim 24.

33. – 36. (Canceled).

37. (Currently Amended) A dryer, comprising:  
a cabinet;



Reply to Office Action of September 11, 2007

a drum provided in the cabinet and ~~configured to be in~~ rotational communication with a motor; and

a heater assembly coupled to the drum, comprising:

a heater case having an air passage formed therein;

a plate ~~configured~~ positioned in the heater case so as to partition the air passage into an upper passage and a lower passage; and

independent first and second coil arrays provided in the air passage ~~and each configured to cross the plate between the upper and lower passages~~, wherein the first coil array ~~comprises~~ crosses the plate multiple times so as to alternately position a plurality of first coils ~~alternately positioned thereof~~ in the upper and lower passages, and the second coil array ~~comprises~~ crosses the plate multiple times so as to alternately position a plurality of second coils ~~alternately positioned thereof~~ in the upper and lower passages such that the first and second coils positioned in the upper passage form an alternating pattern, and the first and second coils positioned in the lower passage form an alternating pattern, wherein each of the plurality of first coils is positioned substantially directly across from a corresponding second coil of the plurality of second coils on the opposite side of the plate, and wherein upper and lower portions of each of the first and second coil arrays ~~lie on~~ are positioned along centerlines of the upper and lower passages, respectively.

38. (Previously Presented) The dryer as claimed in claim 1, wherein at least one of the plurality of first coils is positioned between two adjacent second coils, and at least one of the plurality of second coils is positioned between two adjacent first coils in each of the upper and lower passages.

39. (Previously Presented) The heater assembly as claimed in claim 10, wherein at least one of the plurality of first coils is positioned between two adjacent second coils, and at least one of the plurality of second coils is positioned between two adjacent first coils in each of the upper and lower passages.

40. (Previously Presented) The dryer as claimed in claim 37, wherein at least one of the plurality of first coils is positioned between two adjacent second coils, and at least one of the plurality of second coils is positioned between two adjacent first coils in each of the upper and lower passages.

41. (New) The heater assembly as claimed in claim 10, wherein the independent first and second coil arrays each alternately cross the plate between the upper and lower passages multiple times so as to form the alternating patterns of first and second coils in the upper and lower passages.